

Package: deckroadmap (via r-universe)

June 5, 2026

Title Roadmap Footers for 'Reveal.js' Slides in 'Quarto' and 'R Markdown'

Version 0.1.5.9000

Description Adds section-aware roadmap footers to 'Reveal.js' slide decks created with 'Quarto' or 'R Markdown'. The footer highlights completed, current, and upcoming sections as slides advance. Supports multiple visual styles, inherited section tags, roadmap-free slides, and configurable colors, size, and positioning options.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Imports htmltools

Suggests knitr, rmarkdown, revealjs, quarto, testthat, spelling

URL <https://github.com/CodingTigerTang/deckroadmap>,
<https://codingtigertang.github.io/deckroadmap/>

BugReports <https://github.com/CodingTigerTang/deckroadmap/issues>

VignetteBuilder knitr

Language en-US

Repository <https://codingtigertang.r-universe.dev>

Date/Publication 2026-06-05 17:51:46 UTC

RemoteUrl <https://github.com/CodingTigerTang/deckroadmap>

RemoteRef HEAD

RemoteSha 27647087fd1f4b34c6deecab8e51de70859bf81eb

Contents

preview_roadmap	2
use_roadmap	3

preview_roadmap	<i>Preview a roadmap footer style</i>
-----------------	---------------------------------------

Description

Preview a roadmap footer style

Usage

```
preview_roadmap(
  sections,
  current = sections[1],
  style = c("pill", "minimal", "progress"),
  font_size = "16px",
  bottom = "16px",
  active_color = NULL,
  done_color = NULL,
  todo_color = NULL,
  active_bg_color = NULL,
  done_bg_color = NULL,
  todo_bg_color = NULL
)
```

Arguments

sections	Character vector of section names in order.
current	The current section name to highlight.
style	Roadmap style. One of "pill", "minimal", or "progress".
font_size	CSS font size for the roadmap footer.
bottom	CSS bottom offset for the roadmap footer.
active_color	CSS text color for the active section.
done_color	CSS text color for completed sections.
todo_color	CSS text color for upcoming sections.
active_bg_color	CSS background color for the active section in progress style.
done_bg_color	CSS background color for completed sections in progress style.
todo_bg_color	CSS background color for upcoming sections in progress style.

Value

A browsable HTML preview.

Examples

```
# Preview the default pill style
if (interactive()) {
  preview_roadmap(
    sections = c("Intro", "Problem", "Analysis", "Recommendation", "Next Steps"),
    current = "Analysis"
  )

# Preview the progress style with custom colors
preview_roadmap(
  sections = c("Intro", "Problem", "Analysis", "Recommendation", "Next Steps"),
  current = "Analysis",
  style = "progress",
  active_color = "#ffffff",
  done_color = "#ffffff",
  todo_color = "#334155",
  active_bg_color = "#2563eb",
  done_bg_color = "#475569",
  todo_bg_color = "#e2e8f0"
)
}
```

use_roadmap

Add a roadmap footer to Reveal.js slides

Description

Add a roadmap footer to Reveal.js slides

Usage

```
use_roadmap(
  sections,
  id = "roadmap-config",
  style = c("pill", "minimal", "progress"),
  font_size = "16px",
  bottom = "16px",
  active_color = NULL,
  done_color = NULL,
  todo_color = NULL,
  active_bg_color = NULL,
  done_bg_color = NULL,
  todo_bg_color = NULL,
  inherit_tags = TRUE
)
```

Arguments

sections	Character vector of section names in order.
id	HTML id for the hidden config node.
style	Roadmap style. One of "pill", "minimal", or "progress".
font_size	CSS font size for the roadmap footer.
bottom	CSS bottom offset for the roadmap footer.
active_color	CSS text color for the active section.
done_color	CSS text color for completed sections.
todo_color	CSS text color for upcoming sections.
active_bg_color	CSS background color for the active section in progress style.
done_bg_color	CSS background color for completed sections in progress style.
todo_bg_color	CSS background color for upcoming sections in progress style.
inherit_tags	Logical; if TRUE, untagged slides inherit the most recent data-roadmap value. Use data-roadmap="none" on a slide to hide the roadmap entirely for that slide.

Value

An HTML tag with attached dependencies.

Examples

```
# Add a simple roadmap footer
use_roadmap(
  sections = c("Intro", "Problem", "Analysis", "Recommendation", "Next Steps")
)

# Customize the progress style
use_roadmap(
  sections = c("Intro", "Problem", "Analysis", "Recommendation", "Next Steps"),
  style = "progress",
  active_color = "#ffffff",
  done_color = "#ffffff",
  todo_color = "#334155",
  active_bg_color = "#2563eb",
  done_bg_color = "#475569",
  todo_bg_color = "#e2e8f0"
)
```

Index

`preview_roadmap`, [2](#)

`use_roadmap`, [3](#)